


Features

XLC (XENO Lithium Ion Capacitor)

- Low Self Discharge
- High Operating Voltage
- Wide Operating Temperature Range
- High Capacitance



Drawing



Size	1320
D (Φ)	13.0 +1.5 Max
L (mm)	20.0 ±1.5
d (Φ)	0.6 ±0.1
P (mm)	5.0 ±0.5

Specification

Item	Spec. value	Test methods
Operating Voltage Range	2.5V to 4.0V	
Operating Temp. Range	-25 ~ 85°C (-40 ~ 85°C @ in Li/SOCL2 battery system)	
Load Life @ 85°C	Capacitance : ± 30% of initial value ESR : Less than 200% of initial spec. Appearance : No abnormality	Temperature: 85±2°C Time : 1,000 hours Voltage : 4.0V and measure the floating charge characteristics after returning to normal temperature and humidity.
Heat cycle characteristics		Temperature: 85±2°C, -40±2°C Duration: 30 min Cycle Numbers: 100 cycles
Cycle Life		Temperature : 25±2°C Cycle Number : 50,000 Discharge Current : 20 C-rate Cut-off Voltage : 2.5V (DOD 100%)
Low Temperature characteristics		Capacitance : ± 50% of initial value ESR : Less than 20 times of initial spec.

Part Number	Max Charge Voltage(V)	Rated Capacitance (F)	ESR _{DC} (mΩ)	ESR _{AC} (mΩ)	Leakage Current (μA)	Self Discharge (V)	Rated Current (A)	Pulse Current (A)	Weight (g)
XLC-1320	4.0	120 @ 25°C #1	180 @ 25°C 1sec	90 @ 25°C 1kHz	3 @ 25°C 72hr	Over 97% @ 25°C #1	0.5 @ 25°C	2.5 @ 25°C #2	≤ 5.0g

#1 Reference IEC62813 4.2
#2 1sec. Discharge to 3.2V